

# SAFETY DATA SHEET

according to the Globally Harmonized System

## BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Information  
 Trade name : BUTANOX M-60

Use of the Substance/Mixture : Specific use(s): Curing agent

Company : Nouryon Functional Chemicals B.V.  
 Haaksbergweg 88  
 NL 1101 BZ Amsterdam  
 Netherlands

Telephone : +31889840367  
 Telefax :  
 E-mail address : polymer.emeia@nouryon.com  
 Emergency telephone number : 24 hours:+31 57 06 79211, US-CHEMTREC:1-800-424-9300,  
 CA-CANUTEC:1-613-996-6666, JP: +81 (836) 74 8810, CN:  
 化学事故应急咨询电话 : +86 532 8388 9090-:  
 Nouryon Emergency Response Centre: +31 570 679211

### 2. HAZARDS IDENTIFICATION

#### GHS-Classification

Organic peroxides, Type D  
 Acute toxicity, Category 4, Oral  
 Acute toxicity, Category 4, Inhalation  
 Acute toxicity, Category 5, Dermal  
 Skin corrosion, Sub-category 1B  
 Serious eye damage, Category 1  
 Short-term (acute) aquatic hazard, Category 2

#### GHS-Labeling

Hazard pictograms : 

Signal word : Danger

Hazard statements : H242 Heating may cause a fire.

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

H302 + H332 Harmful if swallowed or if inhaled.  
H313 May be harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H401 Toxic to aquatic life.

## Precautionary statements

### : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P234 Keep only in original packaging.

P235 Keep cool.

P240 Ground and bond container and receiving equipment.

P261 Avoid breathing mist or vapours.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### **Response:**

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P312 Call a POISON CENTER/ doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

### **Storage:**

P403 Store in a well-ventilated place.

P405 Store locked up.

P410 Protect from sunlight.

P420 Store separately.

### **Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

## Other hazards which do not result in classification

No further data available.

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Substance

### Hazardous components

Chemical name	CAS-No.	GHS Classification	Concentration[%]
Dimethyl phthalate	131-11-3	Aquatic Acute 3; H402	55 - 70
Methyl ethyl ketone peroxide; Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane	1338-23-4	Org. Perox. A; H240 Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 5; H313 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Acute 2; H401	30 - 39
Methyl ethyl ketone	78-93-3	Flam. Liq. 2; H225 Acute Tox. 5; H303 Eye Irrit. 2A; H319 STOT SE 3; H336	1 - 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 4. FIRST AID MEASURES

- General advice : Immediate medical attention is required.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.
- Inhalation : If breathed in, move person into fresh air.  
Consult a physician after significant exposure.
- Skin contact : Take off contaminated clothing and shoes immediately.  
Rinse immediately with plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- Eye contact : Rinse with plenty of water.  
Get medical attention immediately. Continue to rinse during transport.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
- Ingestion : Clean mouth with water and drink afterwards plenty of water.  
Never give anything by mouth to an unconscious person.  
Take victim immediately to hospital.

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

Do not induce vomiting! May cause chemical burns in mouth and throat.

## Notes to physician

- Symptoms : The symptoms and effects are as expected from the hazards as shown in section 2. No specific product related symptoms are known.
- Risks : Harmful if swallowed or if inhaled.  
May be harmful in contact with skin.  
Causes serious eye damage.  
Causes severe burns.
- Treatment : Treat symptomatically.

---

## 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Specific hazards during firefighting / Specific hazards arising from the chemical : CAUTION: reignition may occur.  
Supports combustion.  
Water spray may be ineffective unless used by experienced firefighters.  
Do not allow run-off from fire fighting to enter drains or water courses.  
Hazardous decomposition products formed under fire conditions.
- Combustion products : Fire will produce smoke containing hazardous combustion products (see section 10).
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.  
Wear respiratory protection.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Emergency measures on accidental release : Evacuate personnel to safe areas.  
Only qualified personnel equipped with suitable protective

- equipment may intervene.  
Prevent unauthorised persons entering the zone.
- Environmental precautions : Prevent product from entering drains.  
Discharge into the environment must be avoided.
- Methods for cleaning up /  
Methods for containment : Soak up with inert absorbent material and dispose of as hazardous waste.  
Use only inert inorganic material such as vermiculite or perlite as absorbent.  
Keep mixture of absorbent material and spilled product wetted with water.  
Confinement must be avoided.  
Never return spills in original containers for re-use.
- Reference to other sections : For disposal considerations see section 13.  
  
For personal protection see section 8.

---

## 7. HANDLING AND STORAGE

### Handling

- Advice on safe handling : For personal protection see section 8.  
Avoid formation of aerosol.  
Do not breathe vapours or spray mist.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Use explosion protected equipment.  
Keep away from sources of ignition - No smoking.  
No sparking tools should be used.  
Keep away from reducing agents (e.g. amines), acids, alkalies and heavy metal compounds (e.g. accelerators, driers, metal soaps).  
Do not cut or weld on or near this container even when empty.  
Keep away from combustible material.
- Temperature class : It is recommended to use electrical equipment of temperature group T3. However, autoignition can never be excluded.

### Storage

- Requirements for storage areas and containers : No smoking.  
Keep in a well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep only in original container.  
Store away from other materials.
- Maximum storage temperature: : 25 °C

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

Other data : No decomposition if stored and applied as directed.

Maximum storage temperature is for quality only.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dimethyl phthalate	131-11-3	CMP	5 mg/m <sup>3</sup>	AR OEL
		TWA	5 mg/m <sup>3</sup>	ACGIH
Methyl ethyl ketone peroxide; Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane	1338-23-4	CMP-C	0,2 ppm	AR OEL
		C	0,2 ppm	ACGIH
Methyl ethyl ketone	78-93-3	CMP	200 ppm	AR OEL
		CMP - CPT	300 ppm	AR OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Formic acid	64-18-6	CMP	5 ppm	AR OEL
		CMP - CPT	10 ppm	AR OEL
		TWA	5 ppm	ACGIH
		STEL	10 ppm	ACGIH
Acetic acid	64-19-7	CMP	10 ppm	AR OEL
		CMP - CPT	15 ppm	AR OEL
		TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
Propionic acid	79-09-4	CMP	10 ppm	AR OEL
		TWA	10 ppm	ACGIH
Methyl ethyl ketone	78-93-3	CMP	200 ppm	AR OEL
		CMP - CPT	300 ppm	AR OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Methyl ethyl ketone	78-93-3	MEK: 2 mg/l (Urine)	End of shift	Argentina. Biological Exposure Indices

Engineering measures : Explosion proof ventilation recommended.

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

Effective exhaust ventilation system  
Ensure that eyewash stations and safety showers are close to the workstation location.

## Personal protective equipment

- Respiratory protection : In the case of vapour or aerosol formation use a respirator with an approved filter.  
Filter A
- Hand protection
- Material : Neoprene
- Material : Nitrile rubber
- Material : butyl-rubber
- Break through time :  $\geq$  480 min
- Glove thickness : 0,5 mm
- Remarks : Breakthrough time is not determined for the product. Change gloves often!  
The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
- Eye protection : Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Protective suit
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

## Environmental exposure controls

- General advice : Prevent product from entering drains.  
Discharge into the environment must be avoided.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : Faint.
- Odour Threshold : No data available

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

---

pH	:	Weakly acidic
Melting point	:	<= -10 °C
Boiling point/boiling range	:	Decomposes below the boiling point.
Flash point	:	Above the SADT value No flash point was obtained, but the product may release flammable vapour.
Evaporation rate	:	No data available
Flammability (liquids)	:	Decomposition products may be flammable.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	not determined
Relative vapour density	:	No data available
Relative density	:	1,17 (20 °C)
Bulk density	:	Not applicable
Solubility(ies)		
Water solubility	:	partly miscible (20 °C)
Solubility in other solvents	:	(20 °C) Miscible with:, Phthalates
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	Test method not applicable
Decomposition temperature	:	SADT - (Self accelerating decomposition temperature) is the lowest temperature at which self accelerating decomposition may occur with a substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by thermal decomposition at and above the SADT. Contact with incompatible substances can cause decomposition below the SADT.
Self-Accelerating decomposition temperature (SADT)	:	60 °C
Viscosity		
Viscosity, dynamic	:	25 mPa.s ( 20 °C)
Viscosity, kinematic	:	21,37 mm <sup>2</sup> /s ( 20 °C)

---



# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

Explosive properties	: Not explosive
Oxidizing properties	: Not classified as oxidising.
Active Oxygen Content	: 9,8 - 10,0 %
Organic peroxides	: 36 %

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

---

## 10. STABILITY AND REACTIVITY

Conditions to avoid	: Confinement must be avoided. Heat, flames and sparks.
Materials to avoid	: Contact with the following incompatible materials will result in hazardous decomposition: Acids and bases Iron Copper Reducing agents Heavy metals Rust Do not mix with peroxide accelerators, unless under controlled processing. Use only stainless steel 316, PP, polyethylene or glass-lined equipment. For queries regarding the suitability of other materials please contact the supplier.
Hazardous decomposition products	: Formic acid Acetic acid Propionic acid Methyl ethyl ketone Carbon oxides
Thermal decomposition	: SADT - (Self accelerating decomposition temperature) is the lowest temperature at which self accelerating decomposition may occur with a substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by thermal decomposition at and above the SADT. Contact with incompatible substances can cause decomposition below the SADT.
Reactivity	: Stable under normal conditions.
Chemical stability	: Stable under recommended storage conditions.
Hazardous reactions	: No dangerous reaction known under conditions of normal use.
Self-Accelerating decomposition temperature (SADT)	: 60 °C

---

## 11. TOXICOLOGICAL INFORMATION

### PRODUCT INFORMATION:

#### Hazard Summary

Acute toxicity	:	Harmful if swallowed or if inhaled. May be harmful in contact with skin.
Skin corrosion/irritation	:	Causes severe burns.
Serious eye damage/eye irritation	:	Causes serious eye damage.
Respiratory or skin sensitisation	:	Respiratory sensitisation: Not classified based on available information. Skin sensitisation: Not classified based on available information.
Germ cell mutagenicity	:	Not classified based on available information.
Carcinogenicity	:	Not classified based on available information.
Reproductive toxicity	:	Not classified based on available information.
STOT - single exposure	:	Not classified based on available information.
STOT - repeated exposure	:	Not classified based on available information.
Aspiration hazard	:	Not classified based on available information.

#### Potential Health Effects

Inhalation	:	Inhalation of aerosols may cause irritation to mucous membranes. Thermal decomposition can lead to release of irritating gases and vapours. Harmful if inhaled.
Skin	:	Symptoms may be delayed. May be harmful in contact with skin. Causes severe skin burns.
Eyes	:	Causes serious eye damage.
Ingestion	:	Harmful if swallowed. Causes burns.
Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	The symptoms and effects are as expected from the hazards as shown in section 2. No specific product related symptoms are known.

#### Toxicology Assessment

Further information	:	No further data available.
---------------------	---	----------------------------

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

## Test result

Acute oral toxicity	: LD50 Oral: 1.017 mg/kg Species: Rat Method: OECD Test Guideline 401
Acute inhalation toxicity	: LC50 (Rat): 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Acute dermal toxicity	: LD50 Dermal: 4.000 mg/kg Species: Rabbit Method: OECD Test Guideline 402
Skin irritation	: Species: Rabbit Result: Sub-category 1B Classification: Category 1B Method: Tested according to Annex V of Directive 67/548/EEC.
Eye irritation	: Species: Rabbit Result: Risk of serious damage to eyes. Classification: Risk of serious damage to eyes. Method: Tested according to Annex V of Directive 67/548/EEC.

## TOXICOLOGY DATA FOR THE COMPONENTS:

### Toxicology Assessment

#### **Component: Dimethyl phthalate**

Further information : No further data available.

## Test result

#### **Component: Dimethyl phthalate**

Acute oral toxicity	: LD50: > 5.000 mg/kg Species: Rat
Acute inhalation toxicity	: Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50: > 10.000 mg/kg Species: Rabbit
Skin irritation	: Result: slight irritation
Eye irritation	: Result: Slightly irritating to eyes.

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

Aspiration toxicity : No aspiration toxicity classification

**Component: Methyl ethyl ketone peroxide;Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane**

Acute oral toxicity : LD50: 1.017 mg/kg

Species: Rat

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: no

Acute dermal toxicity : LD50: 4.000 mg/kg

Species: Rabbit

Method: OECD Test Guideline 402

Skin irritation : Result: Causes burns.

Eye irritation : Result: Risk of serious damage to eyes.

Germ cell mutagenicity

Genotoxicity in vitro

: Ames test

Result: negative

Genotoxicity in vivo

: Not classified due to data which are conclusive although insufficient for classification.

Carcinogenicity

: No data available

Reproductive toxicity/Fertility

: Species: Rat, male and female

Application Route: Oral

Dose: 0, 25, 50, 75 milligram per kilogram

General Toxicity - Parent: No observed adverse effect level:

50 mg/kg bw/day

General Toxicity F1: No observed adverse effect level F1: 50

mg/kg bw/day

Fertility: No observed adverse effect level Parent: 75 mg/kg

bw/day

Method: OECD Test Guideline 421

GLP: yes

Target Organ Systemic

Toxicant - Repeated

exposure

: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity

: No aspiration toxicity classification

**Component: Methyl ethyl ketone**

Acute oral toxicity : LD50: 2.737 mg/kg

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

	Species: Rat
Acute dermal toxicity	: LD50: 6.480 mg/kg Species: Rabbit
Skin irritation	: Result: Repeated exposure may cause skin dryness or cracking. Moderately irritating.
Eye irritation	: Result: Irritating to eyes.
Target Organ Systemic Toxicant - Single exposure	: Exposure routes: Inhalation The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.
Aspiration toxicity	: No aspiration toxicity classification

---

## 12. ECOLOGICAL INFORMATION

### PRODUCT INFORMATION:

#### Ecotoxicology Assessment

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

### COMPONENTS:

#### Ecotoxicology Assessment

##### Component: Dimethyl phthalate

Short-term (acute) aquatic hazard : Harmful to aquatic life.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life.

### Test result

##### Component: Dimethyl phthalate

#### Ecotoxicity effects

Toxicity to fish : LC50: 420 mg/l  
Exposure time: 96 h  
Species: Lepomis macrochirus (Bluegill sunfish)

Toxicity to algae : EC10: 193,09 mg/l  
Exposure time: 72 h  
Species: Desmodesmus subspicatus (green algae)  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201

ErC50: 259,76 mg/l

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

Exposure time: 72 h  
Species: *Desmodesmus subspicatus* (green algae)  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 11 mg/l  
Exposure time: 102 d  
Species: *Oncorhynchus mykiss* (rainbow trout)  
Test Type: flow-through test  
Method: Other guidelines

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 9,6 mg/l  
Exposure time: 21 d reproduction rate  
Species: *Daphnia magna* (Water flea)  
Method: Other guidelines

## Elimination information (persistence and degradability)

Bioaccumulation : Species: Fish  
Exposure time: 1 d  
Bioconcentration factor (BCF): 5,4

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 93 - 98 %

## Component: Methyl ethyl ketone peroxide; Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane

### Ecotoxicity effects

Toxicity to fish : LC50: 44,2 mg/l  
Exposure time: 96 h  
Species: *Poecilia reticulata* (guppy)  
Test Type: semi-static test  
Method: OECD Test Guideline 203

NOEC: 18 mg/l  
Exposure time: 96 h  
Species: *Poecilia reticulata* (guppy)  
Test Type: semi-static test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50: 39 mg/l  
Exposure time: 48 h  
Species: *Daphnia magna* (Water flea)  
Test Type: Immobilization  
Method: OECD Test Guideline 202

NOEC: 26,7 mg/l  
Exposure time: 24 h  
Species: *Daphnia magna* (Water flea)  
Test Type: Immobilization  
Method: OECD Test Guideline 202

Toxicity to algae : ErC50: 5,6 mg/l

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

Exposure time: 72 h  
Species: Pseudokirchneriella subcapitata (algae)  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201

NOEC: 2,1 mg/l  
Exposure time: 72 h  
Species: Pseudokirchneriella subcapitata (algae)  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201

Toxicity to bacteria : EC50: 48 mg/l  
Exposure time: 0,5 h  
Species: activated sludge  
Test Type: Respiration inhibition  
Method: Domestic OECD Guideline 209

EC10: 12 mg/l  
Exposure time: 0,5 h  
Species: activated sludge  
Test Type: Respiration inhibition  
Method: Domestic OECD Guideline 209

## **Elimination information (persistence and degradability)**

Bioaccumulation : Bioconcentration factor (BCF): 10,3  
Not expected considering the low log Pow value.

Biodegradability : Result: Readily biodegradable.  
Method: Closed Bottle test

## **Component: Methyl ethyl ketone**

### **Ecotoxicity effects**

Toxicity to fish : LC50: 3.220 mg/l  
Exposure time: 96 h  
Species: Lepomis macrochirus (Bluegill sunfish)

## **Elimination information (persistence and degradability)**

Biodegradability : Result: Readily biodegradable.

---

## **13. DISPOSAL CONSIDERATIONS**

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of contents/container in accordance with local regulation.

Contaminated packaging : Empty remaining contents.

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

Dispose of as unused product.  
Do not burn, or use a cutting torch on, the empty drum.  
Due to the high risk of contamination recycling/recovery is not recommended.  
Follow all warnings even after the container is emptied.

---

## 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

UN/ID No. : UN 3105  
Proper shipping name : Organic peroxide type D, liquid  
(Methyl ethyl ketone peroxide)  
Class : 5.2  
Subsidiary risk : HEAT  
Packing group : Not Assigned  
Labels : 5.2 (HEAT)  
Packing instruction (cargo aircraft) : 570  
Packing instruction (passenger aircraft) : 570  
Environmentally hazardous : no

#### IMDG-Code

UN number : UN 3105  
Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID  
(Methyl ethyl ketone peroxide)  
Class : 5.2  
Packing group : Not Assigned  
Labels : 5.2  
EmS Code : F-J, S-R  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### Land transport

UN number : UN 3105  
Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID  
(Methyl ethyl ketone peroxide)  
Class : 5.2  
Packing group : Not Assigned  
Labels : 5.2  
Environmentally hazardous : no

---

## 15. REGULATORY INFORMATION

### Other international regulations

#### Notification status

TCSI : YES. On the inventory, or in compliance with the inventory  
TSCA : YES. All substances listed as active on the TSCA inventory  
AIIIC : YES. On the inventory, or in compliance with the inventory



# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

DSL	: YES. All components of this product are on the Canadian DSL
ENCS	: YES. On the inventory, or in compliance with the inventory
ISHL	: YES. On the inventory, or in compliance with the inventory
KECI	: YES. On the inventory, or in compliance with the inventory
PICCS	: YES. On the inventory, or in compliance with the inventory
IECSC	: YES. On the inventory, or in compliance with the inventory
NZIoC	: YES. On the inventory, or in compliance with the inventory
TECI	: YES. On the inventory, or in compliance with the inventory

For explanation of abbreviation see section 16.

Further information : none

---

## 16. OTHER INFORMATION

### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H240	: Heating may cause an explosion.
H302	: Harmful if swallowed.
H303	: May be harmful if swallowed.
H313	: May be harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H336	: May cause drowsiness or dizziness.
H401	: Toxic to aquatic life.
H402	: Harmful to aquatic life.

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
AR OEL	: Argentina. Occupational Exposure Limits

ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIH / C	: Ceiling limit
AR OEL / CMP	: TLV (Threshold Limit Value)
AR OEL / CMP - CPT	: STEL (Short Term Limit Value)
AR OEL / CMP-C	: Ceiling value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea

# BUTANOX M-60

Version 2

Revision Date 2021/11/17

Print Date 2023/03/14

AR / EN

Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

## Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

---